1956 12:45

Iron Pipe 108 60. 6º Utility strip/ 6° Utility strip 10 11 201 108* 108* 108 108* 100 100 100 100* South Line (Clacktop) Tron Pipe Horthwest Coarter Stone

(17.75° south of corner post) (15.10° north of fenceline)

West ! Mile corner (No stone found) Established 16.5° south of the south side of concrete post. (1336.9° west) Monnes & Overse

Transfer Fer. S. 1.20

I, Delbert A. Hobson, being duly authorized and licensed as a Registered Professional Engineer within the State of Indiana, do hereby certify that the foregoing plat of survey of Ray Young's First Subdivision is time and correct and represents a part of the east holf of the northwest quarter of section thirty two (32). township fourteen (14) north, range two (2) east of the Second Principal Beridian, Borgan County, Indiana, more particularily described as follows, to-wit:

"ail in Corner Post "N-23,30" Mail in Corner Post South-17.70 g 2 ore. North ! Mile-Lec. 32 2643.6° north of center stone. (In line with fence north and

Center Sec. 32, Y14Y., RZE.

fence west)

Regimning at the center of section thirty two (32) (marked by a stone buried 14"), township and runge aforesaid, run thence northerly on the east line of said northwest quarter a distance of two hundred (200.00) feet; (the northeast corner of the northwest quarter is marked by a stone 2643.6° north of the center of section 32, and in line with fence running west and fence running north); run thence westerly and parallel to the south line of said northwest quarter a distance of thirteen hundred thirty four and four-tenths (1334.4) feet, more or less, to the west line of the east half of said northwest quarter; run thence southerly on said west line a distance of two hundred (200.00) feet to the south line of said northwest ouarter in the center of a blacktop road running east and west; run thence easterly on the south line of the northwest quarter a distance of thirteen hundred thirty four and four-tenths (1334.4) feet to the place of beginning, containing (6.127) acres, more

Said Subdivision consists of (12) lots numbered from (1) to (12) consecutively and inclusive. The location and dimensions of the lots and the location and width of the road are as indicated on the plat in figures denoting feet and decimal fractions thereof.

Witness my hand and seal at Mooresville, Indiana, this 5th day of May, 1956

Delbert A. Hobson

Registered Professional Engineer # 2702

State of Indiana